



PO	TN
----	----

FOR	TANK LEVEL GAUGE
MOUNTING	TOP MOUNTING
ENCLOSURE	WEATHER PROOF
MAX. PRESSURE	ATM kgf/cm ²
MAX. TEMP.	150 °C

ITEM TO BE PREPARED BY USER			
NO.	DESCRIPTION	MATERIAL	REMARKS
101	40A PIPE		
102	25A FLANGE		for top anchor
103	25A NOZZLE PIPE		for top anchor
104	40A FLANGE		for connection
105	40A NOZZLE PIPE		for connection

ITEM TO BE SUPPLIED BY HITROL			
NO.	DESCRIPTION	MATERIAL	REMARKS
1	GAUGE HEAD	AL.C	
2	FLOAT	□ 304 SS □ 316L SS	
3	MEASURING TAPE	316L SS	
4	GUIDE WIRE	□ 304 SS □ 316L SS	∅3
5	GAUGE SUPPORT	□ C.S □ 304 SS □ 316L SS	
6	BOTTOM ANCHOR	□ C.S □ 304 SS □ 316L SS	
7	TOP ANCHOR	□ 316L SS+C.S □ 316L SS+304 SS	
8	TOP ANCHOR FLANGE	□ 304 SS □ 316L SS	25A JIS 10K RF
9	CONNECTION FLANGE	□ AL.C □ 304 SS □ 316L SS	40A JIS 10K RF

TAG NO.	Q'TY	MEASURING RANGE(mm)	SCALE RANGE(mm)	TANK HEIGHT(mm)

NOTE
1. GENERAL TOLERANCE IS ±3mm EXCEPT AS NOTED.

△										HITROL CO., LTD.	SCALE	N.S	UNIT	mm	SHEET NO.	/
△										TITLE	PROJECT					
△										TANK LEVEL GAUGE	DRAWING NO.					
△	2024.08.08	1ST ISSUE	S H KIM	B S SING	J S YANG					HLT-1210	HLT1210-BAA-01					
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY											

A3(410mm x 297mm)

This drawing is the property of HITROL and shall not be copied, communicated, or given for tiers except with our written permission.